

Exhibit A 1/5

MCGRAW-HILL CHEMICAL ENGINEERING SERIES

Editorial Advisory Board

JAMES J. CARBERRY *Professor of Chemical Engineering, University of Notre Dame*

MAX S. PETERS *Dean of Engineering, University of Colorado*

WILLIAM R. SCHDWALTER *Professor of Chemical Engineering, Princeton University*

JAMES WEI *Professor of Chemical Engineering, University of Delaware*

BEST AVAILABLE COPY

Exhibit A 2/5

Chemical Engineers' Handbook

FIFTH EDITION

Prepared by a staff of specialists
under the editorial direction of

Robert H. Perry
Consultant

Cecil H. Chilton
Senior Advisor
Battelle Memorial Institute

INTERNATIONAL STUDENT EDITION

MCGRAW-HILL KOGAKUSHA, LTD.

Tokyo Düsseldorf Johannesburg
London Mexico New Delhi Panama
Rio de Janeiro Singapore Sydney

Exhibit A 3/5

Library of Congress Cataloging in Publication Data

Main entry under title:

Chemical engineers' handbook.

(McGraw-Hill chemical engineering series)

First ed. ed. ed. by John H. Perry; 4th ed. under the editorial direction of Robert H. Perry, Cecil H. Chilton and Sidney D. Kirkpatrick.

1. Chemical engineering—Handbooks, manuals, etc. I. Perry, Robert H., ed. II. Chilton, Cecil Hamilton, 1918- ed. III. Perry, John Howard, 1895- 1953, ed. Chemical engineers' handbook. TP151.C52 1973 660.2'8 73-7800 ISBN 0-07-010474-9

INTERNATIONAL STUDENT EDITION

Exclusive rights by McGraw-Hill Kogakusha, Ltd., for manufacture and export. This book cannot be re-exported from the country to which it is assigned by McGraw-Hill.

Copyright © 1973, 1983 by McGraw-Hill, Inc. All rights reserved.
 Copyright renewed 1982, 1989 by Robert H. Perry.
 Copyright 1940, 1941, 1934 by McGraw-Hill, Inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

PRINTED IN JAPAN

Exhibit A 4/5

List of Contributors

1. J. L. Project Manager, Brown & Root, Inc. (Explosion Studies)
2. R. D. Research Associate, Fluid, Chemical, and Thermal Processes
Institute, (Procter & Gamble Co.)
3. Chemical Engineer, F. I. du Pont de Nemours & Co. (Fluid and Particle)
4. J. S. Ch. E. Director of Chemical Engineering, Hercules Corp. (Chemical)
5. Staff Engineer, Gulf Research and Development Co. (Liquid Fuel)
6. Professor, Department of Mechanical and Industrial Engineering, University of Illinois
7. Systems Research Department, Applied Automation, Inc. (Process Control)
8. Senior Research Specialist, F. I. du Pont de Nemours & Co. (Psychrometry)
9. Manager, Administrative Services Department, American Cyanamid
(Fertilizer Estimation)
10. Ph.D., Professor, Department of Chemical Engineering, Oklahoma State
(Design of Heat Exchangers, Condensers, Reboilers)
11. B.S., Ch. E., Assistant, Crystallization Department, Whiting Corp. (Crystallization Equipment)
12. MS., Project Engineer, Abbott Laboratories. (Batch Distillation)
13. Ph.D., Chemical Engineer, F. I. du Pont de Nemours & Co. (Fluid and Particle)
14. Senior Staff Engineer, Advanced Manufacturing Methods Department, IBM
(Process Simulation)
15. Development Director, Monsanto Karbow-Cheon Systems, Inc. (Process)
16. B.S., Senior Process Engineer, Hercules-Strobel Corp. (Distillation)
17. B.S., Staff Chemist, Alkermes-Spectra, Inc. (Process Simulation and Simulation)

Exhibit A 5/5

S-52 FLUID DYNAMICS




FIG. S-52. Friction factors for transition-region flow across tube banks. [From Bergelin, Brown, and Doberstein, *Trans. Am. Soc. Mech. Engrs.*, 74, 853 (1952).] (Pitch is the minimum center-to-center tube spacing.)

Model	Rows	D_o , in.	Pitch/ D_o
1	10	$\frac{3}{8}$	1.25
2	10	$\frac{7}{8}$	1.25
3	14	$\frac{3}{8}$	1.25
4	10	$\frac{7}{8}$	1.50
5	10	$\frac{7}{8}$	1.50

$$f_t = \frac{0.57}{(N_{Re})^{0.25}} \quad (S-157)$$

where $(N_{Re})_v = D_o V_{max} / \mu$, dimensionless; D_o = volumetric hydraulic diameter $[(4 \times \text{free-bundle volume}) / (\text{exposed surface area of tubes})]$, ft.; P = pitch ($= \alpha$ for in-line arrangements, $= \delta$ or α , whichever is smaller, for staggered arrangement), ft.; other quan-

tities as defined following Eq. (S-155). Bergelin et al. show that pressure drop per row is independent of the number of rows in the bank with laminar flow. Equations (S-166) and (S-167) will predict the pressure drop within about ± 25 per cent.

The validity of extrapolating Eq. (S-168) to pitch ratios larger than 1.50 is not known. The correlation of Guntier and Shaw (*loc. cit.*) can be used as an approximation for such cases.

For the laminar flow of non-Newtonian solutions across tube banks, see Adams and Bell (*Chem. Eng. Progr.*, 54, Symp. Ser. 82, 133-145 (1958)).

BEDS OF SOLIDS

Fixed Beds of Granular Solids. Pressure-drop data on the flow of fluids through beds of granular solids are not readily correlated because of the variety of granular materials and of their packing arrangement. For the flow of a single incompressible fluid through a bed of granular solids, the pressure drop or other flow characteristics can be predicted from the correlation given by Leva (*Chem. Eng.*, 56(5), 115-117 (1949), or "Fluidization," McGraw-Hill, New York, 1959). In this correlation,

$$\Delta p = \frac{2f_m G^2 L (1 - \epsilon)^{2-n}}{D_p \rho_s (1 - \epsilon_s)^2} \quad (S-168)$$

where Δp = pressure drop, lb. force/sq. ft.; L = depth of bed, ft.; ϵ_s = dimensional constant, 32.17 (lb./ft.)/(lb. force)(sec.²); D_p = average particle diameter, defined as the diameter of a sphere of the same volume as the particle, ft.; ϵ = voidage (fractional free volume), dimensionless; n = exponent, a function of the modified Reynolds number N'_{Re} , given in Fig. S-49, dimensionless; ϕ = shape factor of the solid, defined as the quotient of the area of a sphere equivalent to the volume of the particle divided by the actual surface of the particle, dimensionless; C = fluid superficial mass velocity based on empty chamber cross section, lb./sq. ft.; ρ = fluid density, lb./cu. ft.; f_m = friction factor, a function of N'_{Re} , given in Fig. S-68. The modified Reynolds number N'_{Re} is defined as

$$N'_{Re} = \frac{D_p C}{\mu} \quad (S-169)$$

where μ = fluid viscosity, lb./ft. (sec.).




FIG. S-49. Friction factor for beds of solids. (Leva, "Fluidization," p. 49, McGraw-Hill, New York, 1959.)